

Rooms 1,3,5,6,7,8,9
and 13-18Vinyl Tiles
Installed
Summer 2002

Guse



MATERIAL SAFETY DATA SHEET

SECTION 1: IDENTIFICATION OF PRODUCT

TRADE NAME: AB COLORS PLUS

PRODUCT NUMBER: FORTRESS MOT-507828 A ITEM: CFE-11-A11 (ref.)
MOT-507817 A
CFE-502011 A

COLOR/THRU CTM-500322 B ITEM: ACT-13-A11 (ref.)
ANA-501013 BP

PLAIN ANP-500056 P ITEM: DVP-56-A11 (ref.)

HERITAGE ST. AHS-503031 D ITEM: CHS-31-A11 (ref.)

WHMIS CLASS: NOT CONTROLLED

DESCRIPTION: POLYVINYL CHLORIDE

PRODUCT USE: FLOOR TILES

TRANSPORT:

HMS CODE: HEALTH () FIRE () REACTIVITY ()
SPECIFIC ()
0:Minor 1:Light 2:Moderate 3:High 4:Dangerous

SUPPLIER:

American Biltrite (Canada) Ltd.
200 Bank Street, Sherbrooke, Québec, Canada, J1H 4K3
EMERGENCY PHONE NUMBER: (819) 829-3300

SECTION 2: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	#CAS	%	T.L.V.	LD50
COPOLYMER VINYL ACETATE AND VINYL CHLORIDE	9003-22-9	10-30	10 mg/m ³ Total dust	
DIOCTYL PHTHALATE (DOP)	117-81-7	1-5	5 mg/m ³	10.6 g/kg (rat oral)
NON-ASBESTOS TREMOLITE	14567-73-8	0.1 - 1.0	10 mg/m ³	
LIMESTONE	1317-65-3	7-10	10 mg/m ³	
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 - 1.0	0.1 mg/m ³	7,950 mg/kg

C0182/PLU/0002 1302-0101/001

AMERICAN BILTRITE

02 09/16 10:01 FAX

TRADE NAME: AB COLORS PLUS

2/4

SECTION 3: PHYSICAL PROPERTIES

APPEARANCE AND ODOUR:	Solid material with different colours
BOILING POINT (°C):	N/A
SPECIFIC GRAVITY (H ₂ O=1):	Approx. 2.3
VAPOR DENSITY (Air=1):	N/D
MELTING POINT (°C):	N/D
EVAPORATION RATE:	N/A
SOLUBILITY IN WATER (%):	N/D
VOLATILE MATTER (% Vol.):	N/D
VAPOR PRESSURE (mm of Hg):	N/A
PH:	N/A

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE:	YES ()	NO (x)
IF YES, IN WHICH CONDITIONS:		
FLASH POINT (°C):	391 (PVC)	
METHOD:	N/D	
AUTOIGNITION TEMPERATURE (°C):	454 (PVC)	
FLAMMABLE LIMITS (% VOL. IN AIR):		
LOWER LIMIT:	N/D	UPPER LIMIT: N/D
EXTINGUISHING MEDIA:		
WATER SPRAY (x)	WATER FOG ()	CARBON DIOXIDE ()
FOAM (x)	DRY CHEMICAL (x)	
OTHERS ()		

SPECIAL FIRE FIGHTING PROCEDURES:

Wear positive pressure self-contained breathing apparatus. Personnel not having suitable respiratory protection must leave the area to prevent significant exposure to toxic combustion gases.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

When forced to burn, about 97 % of the combustion gases from vinyl resin will be a combination of HCL, CO, CO₂. they must be considered as toxic.

SECTION 5: REACTIVITY DATA

STABILITY:	UNSTABLE ()	STABLE (x)
CONDITIONS TO AVOID:	None	
HAZARDOUS POLYMERISATION:	MAY OCCUR ()	WILL NOT OCCUR (x)
CONDITIONS TO AVOID:	None	

COLORFLU 990 1167-001-041

AMERICAN BILKITE

02 09/16 10:01 FAX

TRADE NAME: AB COLORS PLUS

3/4

INCOMPATIBILITY (Materials to avoid): None

WATER	()	BASE	()	OXIDIZING AGENTS	()
ACID	()	CORROSIVE	()		
OTHERS	()				

HAZARDOUS DECOMPOSITION PRODUCTS:

When exposed to flame, HCL, CO and CO₂ will be emitted.

SECTION 6: PREVENTIVE MEASURES

VENTILATION:	N/A
RESPIRATORY PROTECTION:	Not required
EYE PROTECTION:	Safety glasses against dust
HAND PROTECTION:	Gloves
OTHER PROTECTIVE EQUIPMENT:	Not required
HANDLING:	N/A
STORAGE:	Store in a dry and cool area.

SECTION 7: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS
RELEASED OR SPILLED:

Reuse or dispose.

WASTE DISPOSAL METHOD:

Follow local, provincial and federal regulations.

OTHER INFORMATION:

SECTION 8: HEALTH HAZARD DATA

ABSORPTION ROUTE:

SKIN (x)
INHALATION (x)EYES (x)
INGESTION ()EFFECTS OF OVEREXPOSURE:

No adverse health effects are expected. The ingredient(s) listed in section 11 are incorporated into the product and will not be released. They are provided for information.

SKIN:

Contact not expected to be harmful.

EYES:

Not expected to be harmful.

INHALATION:

Not expected to be harmful.

INGESTION:

N/A

COLORPLUS 1561-001/002

P.12

AMERICAN BILKITE

02 09/16 10:02 FAX

TRADE NAME: AB COLORS PLUS

4/4

SECTION 9: FIRST AID PROCEDURES

SKIN: Wash with soap and water.

EYES: Flush with water and remove the dirt particles.

INHALATION: Move the person to fresh air, give artificial respiration if necessary.

INGESTION: Call a physician.

SECTION 10: PREPARATION INFORMATION

PREPARED BY: D. Desrochers

REVISION DATE: December 08, 1999

REPLACING OLD VERSION FROM: August 29, 1997

REASON: Sections 1, 2, 3, 10

AMERICAN BILTRITE (CANADA) LTD. has compiled the information and recommendations contained in this Material Safety Data Sheet from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide for himself what safety measures are necessary to safely use this product, either alone or in combination with other products.

N/A: Not applicable
N/E: Not established

N/D: Not determined

MSDS-TEST DATA (1997)

4004

AMERICAN BILTRITE

02 09/18 10:02 FAX